

Initially Issued: 6/20/1978

Authorization No.: 308



This Is To Certify That

RathGibson - Janesville WI Facility
2505 Foster Ave, Janesville, WI 53545

Is hereby authorized to continue to apply the 3-A Symbol to the models of equipment, conforming to 3-A Sanitary Standards for:

Metal Tubing, Number: 33-02, set forth below:

Model Designations: Polished Metal Tubing Per Attached Listing.

Valid through: December 31, 2011

Timothy R. Rugh

Executive Director, 3-A Sanitary Standards, Inc.

The issuance of this authorization for the use of the 3-A Symbol is based upon the voluntary certification, by the applicant for it, that the equipment listed above complies fully with the 3-A Sanitary Standards designated. Legal responsibility for compliance is solely that of the holder of this Certificate of Authorization, and 3-A Sanitary Standards, Inc. does not warrant that the holder of an authorization at all times complies with the provisions of the said 3-A Sanitary Standards. This in no way affects the responsibility of 3-A Sanitary Standards, Inc. to take appropriate action in such cases in which evidence of nonconformance has been established.

Next TPV Inspection/Report due: December 2013

OD (in.)	Wall Thickness (in.)								
0.500	0.028	0.035	0.049	0.065					
0.625	0.028	0.035	0.049	0.065					
0.750	0.028	0.035	0.049	0.065	0.083	0.095			
0.840	0.028	0.035	0.049	0.065	0.083	0.095	0.109	0.120	
0.875	0.028	0.035	0.049	0.065	0.083	0.095	0.109	0.120	
1.000	0.028	0.035	0.049	0.065	0.083	0.095	0.109	0.120	
1.050	0.028	0.035	0.049	0.065	0.083	0.095	0.109	0.120	0.135
1.125	0.028	0.035	0.049	0.065	0.083	0.095	0.109	0.120	0.135
1.250	0.028	0.035	0.049	0.065	0.083	0.095	0.109	0.120	0.135
1.315	0.028	0.035	0.049	0.065	0.083	0.095	0.109	0.120	0.135
1.375	0.028	0.035	0.049	0.065	0.083	0.095	0.109	0.120	0.135
1.500	0.028	0.035	0.049	0.065	0.083	0.095	0.109	0.120	0.135
1.625	0.028	0.035	0.049	0.065	0.083	0.095	0.109	0.120	0.135
1.660	0.028	0.035	0.049	0.065	0.083	0.095	0.109	0.120	0.135
1.750	0.028	0.035	0.049	0.065	0.083	0.095	0.109	0.120	0.135
1.900	0.028	0.035	0.049	0.065	0.083	0.095	0.109	0.120	0.135
2.000	0.028	0.035	0.049	0.065	0.083	0.095	0.109	0.120	0.135
2.125		0.035	0.049	0.065	0.083	0.095	0.109	0.120	0.135
2.250		0.035	0.049	0.065	0.083	0.095	0.109	0.120	0.135
2.375		0.035	0.049	0.065	0.083	0.095	0.109	0.120	0.135
2.500		0.035	0.049	0.065	0.083	0.095	0.109	0.120	0.135
2.625			0.049	0.065	0.083	0.095	0.109	0.120	0.135
2.750			0.049	0.065	0.083	0.095	0.109	0.120	0.135
2.875			0.049	0.065	0.083	0.095	0.109	0.120	0.135
3.000			0.049	0.065	0.083	0.095	0.109	0.120	0.135
3.500			0.049	0.065	0.083	0.095	0.109	0.120	0.135
4.000				0.065	0.083	0.095	0.109	0.120	0.135
6.000					0.083		0.109		
8.000							0.109		

.203
(2.5" S40
Pipe)

0.216
(3" S40
Pipe)

0.226
(3.5" S40
Pipe)